



CHAMPION OF ROUGH ROADS

BOXER *X150*
NOW WITH 5 GEARS



- HIGH POWER
- DURABLE
- COMFORTABLE
- LOW MAINTENANCE
- WIDER SEAT



X150



Available in 3 colours:



Red



Black



Blue

ENGINE

Engine Type	4 stroke, Air cooled, Single Cylinder, SOHC, Single Plug
Displacement (cc)	144.8 cc
Max. Power (Ps @ RPM)	12 PS @ 7500 rpm
Max. Torque (Nm @ RPM)	12.55 NM @ 5000 rpm
Transmission	5 Speed Constant Mesh (All down shift)

CHASSIS AND BODY

Frame Type	Tubular
Front Suspension	Hydraulic, Telescopic, 125 mm travel
Rear Suspension	Hydraulic Twin Suspension, SNS type, 100 mm travel
Wheel -Front & Rear	Alloy
Brakes - Front & Rear	Mechanically Expanding Shoes / Hydraulic Disc Brake
Brake Size - Front & Rear	130 mm Drum Brake / 240 mm Disc Brake
Tyre Front	3.00 - 17", 46P Semi Knobby
Tyre Rear	100/90 - 17", 55P Semi Knobby
Steering-cum-Ignition Lock	Yes
Starting	Kick & Electric Start
Tail Lamp	12V, 21/5W
Blinkers	10 W

FUEL TANK

Fuel Tank Capacity (ltrs)	11 ltrs
Usable Reserve (ltrs)	2.5 ltrs
Unusable Reserve (ltrs)	1 ltr

CONTROLS

Steering	Handlebar	
Accelerator	On Handlebar, RH Grip	
Gears	Left Foot, Pedal Operated	
Brakes	Front Rear	Drum-130 mm Drum-130 mm

ELECTRICALS

System	12V, DC
Battery	12V 4Ah VRLA
Headlamp	12V 35/35W HS1

DIMENSIONS

Wheel Base (mm)	1285
Length (mm)	2016
Height (mm)	1134
Width (mm)	740
Ground Clearance (mm)	190
Kerb Weight (Kg)	125

**For any enquiries
please call on
XXXXX**

Dealer stamp & address

- Accessories shown may not be part of the standard fitment
- Values given above are nominal & for guidance only, 15% variation is allowed to cater for production & measurement
- All dimensions are under un-laden conditions
- Definitions of terminologies wherever applicable are as per relevant IS/ISO standards
- Specifications are subject to change without notice



CHAMPION OF ROUGH ROADS

BOXER *X 150*
NOW WITH 5 GEARS



-  HIGH POWER
-  DURABLE
-  COMFORTABLE
-  LOW MAINTENANCE
-  WIDER SEAT





Available in 3 colours:



ENGINE	
Engine Type	4 stroke, Air cooled, Single Cylinder, SOHC, Single Plug
Displacement (cc)	144.8 cc
Max. Power (Ps @ RPM)	12 PS @ 7500 rpm
Max. Torque (Nm @ RPM)	12.55 NM @ 5000 rpm
Transmission	5 Speed Constant Mesh (All down shift)

CHASSIS AND BODY	
Frame Type	Tubular
Front Suspension	Hydraulic, Telescopic, 125 mm travel
Rear Suspension	Hydraulic Twin Suspension, SNS type, 100 mm travel
Wheel -Front & Rear	Alloy
Brakes - Front & Rear	Mechanically Expanding Shoes / Hydraulic Disc Brake
Brake Size - Front & Rear	130 mm Drum Brake / 240 mm Disc Brake
Tyre Front	3.00 - 17", 46P Semi Knobby
Tyre Rear	100/90 - 17", 55P Semi Knobby
Steering-cum-Ignition Lock	Yes
Starting	Kick & Electric Start
Tail Lamp	12V, 21/5W
Blinkers	10 W

FUEL TANK	
Fuel Tank Capacity (ltrs)	11 ltrs
Usable Reserve (ltrs)	2.5 ltrs
Unusable Reserve (ltrs)	1 ltr

CONTROLS		
Steering		Handlebar
Accelerator		On Handlebar, RH Grip
Gears		Left Foot, Pedal Operated
Brakes	Front	Drum-130 mm
	Rear	Drum-130 mm

ELECTRICALS	
System	12V, DC
Battery	12V 4Ah VRLA
Headlamp	12V 35/35W HS1

DIMENSIONS	
Wheel Base (mm)	1285
Length (mm)	2016
Height (mm)	1134
Width (mm)	740
Ground Clearance (mm)	190
Kerb Weight (Kg)	125

For any enquiries please call on XXXXX

Dealer stamp & address

- Accessories shown may not be part of the standard fitment
- Values given above are nominal & for guidance only, 15% variation is allowed to cater for production & measurement
- All dimensions are under un-laden conditions
- Definitions of terminologies wherever applicable are as per relevant IS/ISO standards
- Specifications are subject to change without notice