







INTRODUCING THE ALL NEW N250 AND N160 WITH DURL CHRITTEL





TECHNICAL SPECIFICATIONS

	SPECIFICATION	PULSAR N250	PULSAR N160
	Туре	Single cylinder, 4 stroke, SOHC,v 2 valve, Oil cooled, Fl	Single cylinder, 4 stroke, SOHC, 2 valve, Oil cooled, Fl
	Displacement	249.07 cc	164.82 cc
	Max. Power	18 kW (24.5 PS) @ 8750 rpm	11.7 kW (16 PS) @ 8750 rpm
	Max. Torque	21.5 Nm @ 6500 rpm	14.65 Nm @ 6750 rpm
	Transmission	Constant mesh 5 speed	Constant mesh 5 speed
BRAKE	Front	300 mm Disc, ABS	300 mm Disc, ABS
	Rear	230 mm Disc	230 mm Disc
	(*Dual Channel ABS variant only in Brooklyn Black colour)		
	Front	Telescopic (37 mm)	
	Rear	Monoshock with Nitrox	
	Front	100/80-17 Tubeless	
	Rear	130/70-17 Tubeless	
	Wheel base	1351 mm	1358 mm
	Seat height – rider	795 mm	
	Ground clearance	165 mm	
	Kerb weight	162 kg	154 kg
	Fuel tank capacity	14 L	
	Console features	Gear indicator, Clock, Fuel economy and Range indicator	
	Head l amp	Bi functional LED projector headlamp with LED DRLs	
	Tail lamp	LED Tail lamp with Glitter pattern	
	Mobi l e Charger	USB connectivity	



SOLE DISTRIBUTOR FOR NEPAL | 1 /PulsarNepal

Hansraj Hulaschand & Co Pvt. Ltd.

GOLCHHA GROUP TEUR TRUST TRUST Url: nepal.globalbajaj.com/en

/PulsarNepal

in /Company/Golchhagroup